

Page 1/9

Revision: 20.02.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 2 (replaces version 1)

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Omnident Härterflüssigkeit für Silikonknetmassen
- · UFI: MXC0-405Q-200C-N5RS
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Dental.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Cavex Holland B. V.

The Netherlands

Supplier:

Omnident Dental-Handelsgesellschaft mbH Gutenbergring 7 - 9 D-63110 Rodgau, Hessen

T 0049 (6106) 874-267

F 0049 (6106) 874-265

www.omnident.de

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: 0049 (6106) 874-267.

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 20.02.2023 Version number 2 (replaces version 1) Revision: 20.02.2023

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

(Contd. of page 1)

· Hazard pictograms





GHS02 GHS07 GHS0

- · Signal word Warning
- · Hazard-determining components of labelling:

tetraethyl silicate

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

Determination of endocrine-disrupting properties

870-08-6 dioctyltin oxide List II

3 Composition/information on ingredients

- · Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

ſ	· Dangerous components:			
ſ		tetraethyl silicate	30-50%	
	EINECS: 201-083-8	🌣 Flam. Liq. 3, H226; 🗘 Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335		
Γ		dioctyltin oxide	30-50%	
	EINECS: 212-791-1	🕸 STOT RE 2, H373; Aquatic Chronic 4, H413		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Printing date 20.02.2023 Version number 2 (replaces version 1) Revision: 20.02.2023

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

(Contd. of page 2)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: < 8 °Celsius.

(Contd. on page 4)

Printing date 20.02.2023

Version number 2 (replaces version 1)

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

(Contd. of page 3)

Revision: 20.02.2023

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-10-4 tetraethyl silicate

OEL Long-term value: 44 mg/m³, 5 ppm IOELV

870-08-6 dioctyltin oxide

OEL Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/the preparation/the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

Printing date 20.02.2023 Version number 2 (replaces version 1) Revision: 20.02.2023

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

(Contd. of page 4)

9 Physical and chemical properties

Information on basic physical and chemical properties

· General Information

Physical state Colour: Red

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 110 °C • Flammability Flammable.

· Lower and upper explosion limit

Lower:
Upper:
1.3 Vol % (78-10-4 tetraethyl silicate)
Upper:
23 Vol % (78-10-4 tetraethyl silicate)

• Flash point: 28 °C
• Ignition temperature: 234 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 1.7 hPa (78-10-4 tetraethyl silicate)

Density and/or relative density

Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.

· Other information

· Appearance:

· Form: Pasty
· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 0.00 % *· Solids content:* 24.7 %

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

· Substances and mixtures, which emit flammable

gases in contact with water Void

(Contd. on page 6)

Printing date 20.02.2023 Version number 2 (replaces version 1) Revision: 20.02.2023

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

(Contd. of page 5)

· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:					
	78-10-4 tetraethyl silicate				
Oral	LD50	6,270 mg/kg (rat)			
Dermal	<i>LD50</i>	5,878 mg/kg (rabbit)			

- · Primary irritant effect: -
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Information on other hazards
- · Endocrine disrupting properties

870-08-6 dioctyltin oxide

List II

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 7)

Printing date 20.02.2023 Version number 2 (replaces version 1) Revision: 20.02.2023

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

(Contd. of page 6)

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

TIAT I ID I	
UN number or ID number ADR, IMDG, IATA	UN1993
UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. (TETRAETH
DAD C. LATA	SILICATE)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (TETRAETHYL SILICATE)
Transport hazard class(es)	
ADR, IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	A
Maritime transport in bulk according to IMO	
instruments	Not applicable.
Transport/Additional information:	
4DR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transpart category	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	D/E
IMDG Limited quantities (LQ)	<i>5L</i>

Printing date 20.02.2023 Version number 2 (replaces version 1) Revision: 20.02.2023

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

	(Contd. of page 7)
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TETRAETHYL SILICATE), 3, III

15 Regulatory information

- · Directive 2004/42/EC
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20
- · Regulation (EU) No 649/2012

870-08-6 dioctyltin oxide

Annex I Part 1

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Product safety department
- · Contact: .
- · Version number of previous version: 1
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 9)

Printing date 20.02.2023

Version number 2 (replaces version 1)

Trade name: Omnident Härterflüssigkeit für Silikonknetmassen

(Contd. of page 8)

Revision: 20.02.2023

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4